



QC STL PRO-4.8X
QuietCool Stealth Pro Line

QC STL PRO-4.8X Specifications

| | | |
|--|---|--|
| Motor Voltage | 120 VAC, 60 Hz | |
| Energy Use | Hi: 408 Watts / Med: 225 Watts / Low: 73.9 Watts | |
| Air Flow | Hi: 4280 CFM / Med: 3500 CFM / Low: 2361 CFM | |
| HVI-916 Airflow (for CA Title 24 New Construction) | Hi: 3130 CFM / Med: 2560 CFM / Low: 1670 CFM | |
| dBA | Hi: 47.4 / Med: 43.2 / Low: 33.0 | |
| Recommended SQFT Coverage @ 2-3 CFM per SQFT | Covers 1427 SQFT to 2140 SQFT | |
| Minimum Attic Clearance | 36" | |
| # of Speeds | 3 | |
| Duct Diameter | 18" | |
| Duct Length | 9 feet | |
| Motor Head Diameter | 18 1/2" | |
| Motor Head Length | 13 1/2" | |
| Dampers | Barometric Pressurized R5 Dampers | |
| Controls | Included: 8 Hr Electronic Timer & Double 3-way switch Optional: IT-36002 QuietCool RF Wireless Control Kit | |
| Warranty | 15 Years | |
| Framing | None Required | |
| Joist Cutting | None Required; fits 16" or 24" on center | |
| Minimum Suggested Attic Venting | 5.71 SQ FT net free area | |
| Ceiling Rough Opening | 14 1/4" x 30 1/4" | |
| Removable Grille Outside Dimension | 16" x 32" | |
| Shipping Weight | 75 lbs. | |
| Box Dimensions | 36" x 22" x 40" | |
| In The Box | -QC STL PRO-4.8X Motorhead -Removable Grille -Cut-out Template -Window Locks | -Damper Box -9 Foot Duct -Accessory Bag -Controls |



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM