



QC-STL PRO-6.5
QuietCool Stealth Pro Line

QC-STL PRO-6.5 Specifications

Motor Voltage	120 VAC, 60 Hz
Energy Use	Hi/Hi: 569 Watts / Hi/Lo: 344 Watts Hi/Off: 266 Watts / Lo/Off: 76 Watts
Air Flow	Hi: 6035 CFM / Med/Hi: 4897 CFM Med/Low: 3630 CFM / Low: 2323 CFM
HVI-916 Airflow	5660 CFM
Square Foot Coverage @ 2 CFM per SQ FT	Covers up to 3050 SQ FT
# of Speeds	4
Duct Diameter	16"
Duct Length	6 feet
Motor Head Diameter	16 1/2"
Motor Head Length	13 1/2"
Dampers	Barometric Pressurized R5 Dampers
Controls	Included 8 Hour Electronic Timer and Double 3-Way Switch
Warranty	15 Years
Framing	None Required
Joist Cutting	None Required; fits 16" or 24" on center
Minimum Suggested Attic Venting	8.0 SQ FT net free area
Ceiling Rough Opening	14 1/4" x 36 1/4"
Removable Grille Outside Dimension	16" x 38"
Shipping Weight	87 lbs.
Box Dimensions	42" x 20" x 38"
In The Box	-QC STL PRO-6.5 Motorhead -Damper Box -Removable Grille -6 Foot Duct(2) -Cut-out Template -Accessory Bag(2) -Window Locks -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM