

## QC TRI PRO-1.5X Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	115 Watts	
Air Flow	1498 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	1110 CFM	
dBA	Hi: 37.4	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 499 SQFT to 749 SQFT	
Minimum Attic Clearance	32"	
# of Speeds	1	
Duct Diameter	14"	
Duct Length	6 feet	
Motor Head Diameter	14 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included: 8 Hr Electronic Timer Optional: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	2 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 14 1/4"	
Removable Grille Outside Dimension	16" x 16"	
Shipping Weight	43 lbs.	
Box Dimensions	20" x 20" x 38"	
In The Box	-QC TRI PRO-1.5X Motorhead -Removable Grille -Cut-out Template -Window Lock	-Damper Box -6 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:  
[QUIETCOOLSYSTEMS.COM](http://QUIETCOOLSYSTEMS.COM)

QC TRI PRO-1.5X  
QuietCool Trident Pro Line