

QC TRI PRO-3.3X
QuietCool Trident Pro Line

QC TRI PRO-3.3X Specifications

Motor Voltage	120 VAC, 60 Hz	
Energy Use	Hi: 323 Watts / Low: 274 Watts	
Air Flow	Hi: 3216 CFM / Low: 2890 CFM	
HVI-916 Airflow (for CA Title 24 New Construction)	Hi: 2450 CFM / Low: 2230 CFM	
dBA	Hi: 49.4 / Low: 46.8	
Recommended SQFT Coverage @ 2-3 CFM per SQFT	Covers 1072 SQFT to 1608 SQFT	
Minimum Attic Clearance	34"	
# of Speeds	2	
Duct Diameter	16"	
Duct Length	6 feet	
Motor Head Diameter	16 1/2"	
Motor Head Length	13 1/2"	
Dampers	Barometric Pressurized R5 Dampers	
Controls	Included: 8 Hr Electronic Timer & HI-LOW-OFF switch Optional: IT-36002 QuietCool RF Wireless Control Kit	
Warranty	15 Years	
Framing	None Required	
Joist Cutting	None Required; fits 16" or 24" on center	
Minimum Suggested Attic Venting	4.29 SQ FT net free area	
Ceiling Rough Opening	14 1/4" x 22 1/4"	
Removable Grille Outside Dimension	16" x 24"	
Shipping Weight	55 lbs.	
Box Dimensions	27" x 20" x 38"	
In The Box	-QC STL PRO-3.3X Motorhead -Removable Grille -Cut-out Template -Window Locks	-Damper Box -6 Foot Duct -Accessory Bag -Controls



For more information, visit our website at:
QUIETCOOLSYSTEMS.COM